

Page: 1 of 7 Printed: 05/05/2015 Revision: 05/05/2015

Supersedes Revision: 02/22/1999

1. PRODUCT AND COMPANY IDENTIFICATION

Product Code: L-12965

Product Name: Solution 1000 Food Grade Anti-Seize

Company Name: MRO Solutions, LLC Phone Number: 5645 W. Howard St. +1 (847)588-2480

Niles, IL 60714

Web site address: http://www.mrosolutions.com/

Emergency Contact: CHEMTREC +1 (800)424-9300

2. HAZARDS IDENTIFICATION

Acute Toxicity: Oral, Category 5 Skin Corrosion/Irritation, Category 2

Serious Eye Damage/Eye Irritation, Category 2A

Aquatic Toxicity (Acute), Category 1
Aquatic Toxicity (Chronic), Category 1





GHS Signal Word: Warning

GHS Hazard Phrases: H303 - May be harmful if swallowed.

H315 - Causes skin irritation.

H319 - Causes serious eye irritation. H400 - Very toxic to aquatic life.

H410 - Very toxic to aquatic life with long lasting effects.

GHS Precaution Phrases: P264 - Wash hands thoroughly after handling.

P273 - Avoid release to the environment.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

GHS Response Phrases: P302+352 - IF ON SKIN: Wash with plenty of soap and water. P362 - Take off

contaminated clothing and wash before re-use. P332+313 - If skin irritation occurs, get

medical advice/attention.

P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+313 - If eye irritation

persists, get medical advice/attention.

P312 - Call a POISON CENTER or doctor/physician if you feel unwell.

P321 - Specific treatment see Section 4 reference to supplemental first aid instruction - if

immediate measures are required.

P391 - Collect spillage.

GHS Storage and Disposal

Phrases:

P501 - Dispose of contents and containers in accordance with local, regional, national,

and international regulations.

Hazard Rating System:





Page: 2 of 7 Printed: 05/05/2015

Revision: 05/05/2015 Supersedes Revision: 02/22/1999

Potential Health Effects (Acute and Chronic):

Prolonged or repeated skin contact may cause dermatitis. Chronic inhalation and ingestion may cause effects similar to those of acute inhalation and ingestion. Effects

may be delayed.

Hazards not otherwise classified (HNOC) or not covered by GHS. None.

Inhalation: May cause irritation to the respiratory tract. Inhalation of dusts at levels above

recommended exposure limits may cause a metallic or sweet taste.

Skin Contact: May cause mild skin irritation. Prolonged and/or repeated contact may cause irritation

and/or dermatitis.

Eye Contact: Dust may cause mechanical irritation. May cause tearing, redness, and swelling. May

result in corneal injury.

Ingestion: No hazard expected in normal industrial use. May be harmful if swallowed. May cause

gastrointestinal irritation with nausea, vomiting and diarrhea.

3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS#	Hazardous Components (Chemical Name)	Concentration
8042-47-5	White mineral oil	25.0 - 35.0 %
64742-52-5	Aliphatic petroleum distillate	20.0 %
1305-62-0	Hydrated lime	18.0 %
1314-13-2	Zinc oxide	<8.00 %
14807-96-6	Talcum	8.00 %
54326-11-3	Aluminum hydroxide benzoate stearate	2.50 - 5.00 %
112945-52-5	Silica, amorphous treated	3.00 %

4. FIRST AID MEASURES

Emergency and First Aid

Procedures:

In Case of Inhalation:No specific treatment is necessary since this material is not likely to be hazardous by

inhalation. If exposed to excessive levels of dusts or fumes, remove to fresh air and get

medical attention if cough or other symptoms develop.

In Case of Skin Contact: Wash off with soap and plenty of water. Get medical aid if irritation develops or persists.

In Case of Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If

irritation develops, get medical aid.

In Case of Ingestion: Never give anything by mouth to an unconscious person. Rinse mouth with water. Get

medical aid immediately. If victim is fully conscious, give a cupful of water. If conscious and alert, rinse mouth and drink 2-4 cupfuls of milk or water. If victim is conscious and alert, give 2-4 cupfuls of milk or water. Get medical aid if irritation or symptoms occur.

Signs and Symptoms Of

Exposure:

The most important known symptoms and effects are described in the labelling (see

section 2.2) and/or in section 11

Note to Physician: Treat symptomatically and supportively.



Page: 3 of 7
Printed: 05/05/2015
Revision: 05/05/2015

Supersedes Revision: 02/22/1999

5. FIRE FIGHTING MEASURES

Flash Pt: 375 F (191 C) Method Used: Cleveland Open Cup Explosive Limits: LEL: No data. UEL: No data.

Autoignition Pt: No data.

Suitable Extinguishing Media: Use water spray, dry chemical, carbon dioxide, or chemical foam. If water is used, fog

nozzles are preferred.

Fire Fighting Instructions: As in any fire, wear a self-contained breathing apparatus in pressure-demand,

MSHA/NIOSH approved (or equivalent), and full protective gear. Containers can build up pressure if exposed to heat (fire). Containers may explode in the heat of a fire. Use water

spray to keep fire-exposed containers cool.

Flammable Properties and

Hazards:

High temperatures and fire conditions can result in the formation of carbon monoxide and

carbon dioxide, toxic fumes of zinc oxide.

6. ACCIDENTAL RELEASE MEASURES

Protective Precautions, Protective Equipment and Emergency Procedures: Use proper personal protective equipment as indicated in Section 8.

Environmental Precautions: Do not empty into drains. Material that cannot be recovered or reused should be

disposed of in accordance with all Federal, State and Local regulations.

Steps To Be Taken In Case Material Is Released Or

Spilled:

Avoid breathing vapors, mist or gas. Provide ventilation. Remove all sources of ignition. Sweep up or absorb material, then place into a suitable clean, dry, closed container for

disposal.

7. HANDLING AND STORAGE

Precautions To Be Taken in

Handling:

Avoid contact with skin and eyes. Avoid ingestion and inhalation. Wash thoroughly after handling. Remove contaminated clothing and wash before reuse. Use with adequate

ventilation.

Do not reuse empty containers without first having them commercially cleaned or reconditioned. Follow all SDS/label precautions even after container is emptied because

they may retain product residues.

Precautions To Be Taken in

Storing:

Store in a cool, dry, well-ventilated area away from incompatible substances. Store away

from heat. Keep container closed when not in use.

Other Precautions: Keep out of reach of children. Handle in accordance with good industrial hygiene and

safety practices.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CAS#	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
8042-47-5	White mineral oil	No data.	No data.	No data.
64742-52-5	Aliphatic petroleum distillate	No data.	No data.	No data.
1305-62-0	Hydrated lime	PEL: 15 (dust); 5 (resp.) mg/m3	TLV: 5 mg/m3	No data.
1314-13-2	Zinc oxide	PEL: 5 (fume); 15 (dust) mg/m3	TLV: 2 mg/m3 (R) STEL: 10 mg/m3 (R)	No data.
14807-96-6	Talcum	PEL: 706 ppm/20 mppcf	TLV: 2 mg/m3 (non-asbestos)	No data.
54326-11-3	Aluminum hydroxide benzoate stearate	No data.	No data.	No data.



Page: 4 of 7 Printed: 05/05/2015

Revision: 05/05/2015

Supersedes Revision: 02/22/1999

112945-52-5 Silica, amorphous treated

No data.

No data.

No data.

Respiratory Equipment (Specify Type):

Not required under normal use conditions. Avoid breathing vapors or dusts. In restricted areas, use approved chemical/mechanical filters designed to remove a combination of particles and vapor. In confined areas, use approved air line type respirator or hood. Self-contained breathing apparatus is required for vapor concentrations above PEL/TLV

limits.

Eye Protection: Safety glasses, chemical goggles, and/or face shield should be worn.

Protective Gloves: Not required under normal use conditions. Solvent resistant gloves required for prolonged

or repeated contact.

Other Protective Clothing: Wear appropriate protective clothing to minimize contact with skin. Chemical resistant

apron.

Engineering Controls

(Ventilation etc.):

Use adequate general or local exhaust ventilation to minimize exposure levels. Use process enclosure, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Facilities storing or utilizing this

material should be equipped with an eyewash facility and a safety shower.

Work/Hygienic/Maintenance

Practices:

General industrial hygiene practice.

Environmental Exposure

Controls:

Do not let product enter drains.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical States: [] Gas [X] Liquid [X] Solid Appearance and Odor: Appearance: Off-white. Thick. Paste.

Odor: Slight. Petroleum-like.

Melting Point: No data.

Boiling Point: 500 F (260 C) - 611 F (322 C)

Autoignition Pt: No data.

Flash Pt: 375 F (191 C) Method Used: Cleveland Open Cup Explosive Limits: LEL: No data. UEL: No data.

Specific Gravity (Water = 1): 1.11

Density: NA

Vapor Pressure (vs. Air or NA

mm Hg):

Vapor Density (vs. Air = 1): Heavier than air Evaporation Rate: Slower than (Ether=1)

Solubility in Water: NIL Saturated Vapor NA

Concentration:

Viscosity: NA PH: NA

Percent Volatile: No data.



Page: 5 of 7 Printed: 05/05/2015 Revision: 05/05/2015

Supersedes Revision: 02/22/1999

10. STABILITY AND REACTIVITY

Reactivity: High temperatures and fire conditions can result in the formation of carbon monoxide and

carbon dioxide, toxic fumes of zinc oxide.

Stability: Unstable [] Stable [X]

Conditions To Avoid -

High temperatures, Incompatible materials.

Instability:

Incompatibility - Materials To Strong oxidizing agents. Acids.

Avoid:

Hazardous Decomposition or High temperatures and fire conditions can result in the formation of carbon monoxide and

Will not occur [X]

Byproducts:

carbon dioxide, toxic fumes of zinc oxide.

Possibility of Hazardous

Will occur []

Reactions:

Conditions To Avoid - No data available.

Hazardous Reactions:

11. TOXICOLOGICAL INFORMATION

Toxicological Information: Epidemiology: No information available.

Teratogenicity: No information available.

Reproductive Effects: No information available.

Mutagenicity: No information available. Neurotoxicity: No information available.

Other Studies: CAS# 64742-52-5:

Acute toxicity, LD, Oral, Rat, > 5.0 mg/kg

Other Studies: CAS# 8042-47-5: TDLo, Oral, Rat, 92 gm/kg, 92 D.

Other Studies: CAS# 1305-62-0:

Acute toxicity, LD50, Oral, Rat, 7340 mg/kg.

Other Studies: CAS# 1314-13-2:

Acute toxicity, LDLo, Oral, Human, 500 mg/kg.

Other Studies: CAS # 112945-52-5:

Acute toxicity, LD50, Oral, Rat, 3160 mg / kg.

Irritation or Corrosion: Other Studies: CAS# 64742-52-5:

Standard Draize Test, Skin, Species: Rabbit, 500.0 mg.

Sensitization: No data available.

Carcinogenicity: NTP? No IARC Monographs? No OSHA Regulated? No

12. ECOLOGICAL INFORMATION

General Ecological Physical: No information available.

Information: Environmental: No information available.

Results of PBT and vPvB

Other Studies: CAS# 1305-62-0:

assessment:

LC50, Western Mosquitofish (Gambusia affinis), adult(s), 160000 ug/L, 96H, adults.

Other Studies: CAS# 1314-13-2:

LC50, Bluegill (Lepomis macrochirus), 320pm, 96 H.

Persistence and No data available.



Page: 6 of 7 Printed: 05/05/2015 Revision: 05/05/2015

Supersedes Revision: 02/22/1999

Degradability:

Bioaccumulative Potential: No data available.

Mobility in Soil: No data available.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method: Contaminated packaging. Chemical waste generators must determine whether a

discarded chemical is classified as a hazardous waste. US EPA guidelines for the

classification determination are listed in 40 CFR Parts 261. Additionally, waste generators

must consult state and local hazardous waste regulations to ensure complete and

accurate classification.

14. TRANSPORT INFORMATION

LAND TRANSPORT (US DOT):

DOT Proper Shipping Name: Not regulated as a hazardous material.

DOT Hazard Class: UN/NA Number:

LAND TRANSPORT (Canadian TDG):

TDG Shipping Name: No information available.

15. REGULATORY INFORMATION

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS#	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
8042-47-5	White mineral oil	No	No	No
64742-52-5	Aliphatic petroleum distillate	No	No	No
1305-62-0	Hydrated lime	No	No	No
1314-13-2	Zinc oxide	No	No	Yes-Cat. N982
14807-96-6	Talcum	No	No	No
54326-11-3	Aluminum hydroxide benzoate stearate	No	No	No
112945-52-5	Silica, amorphous treated	No	No	No

112945-52-5	Silica, amorphous treated	No	No	No
CAS#	Hazardous Components (Chemical Name)	Other US EPA or State Lists		
8042-47-5	White mineral oil	TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No		
64742-52-5	Aliphatic petroleum distillate	TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No		
1305-62-0	Hydrated lime	TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: Title 8; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: Yes - 0322; NY Part 597: No; PA HSL: Yes - 1; SC TAP: No; WI Air: Yes		
1314-13-2	Zinc oxide	TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: TAC, Title 8; MA Oil/HazMat: Yes - Cat.; MI CMR, Part 5: Part 5; NC TAP: No; NJ EHS: Yes - 2037; NY Part 597: No; PA HSL: Yes - E; SC TAP: No; WI Air: No		
14807-96-6	Talcum		•	DP.65: No; CA TAC, Title 8: CMR, Part 5: No; NC TAP: No;



Page: 7 of 7 Printed: 05/05/2015

Revision: 05/05/2015 Supersedes Revision: 02/22/1999

NJ EHS: Yes - 1773; NY Part 597: No; PA HSL: Yes - 1; SC

TAP: No; WI Air: Yes

54326-11-3 Aluminum hydroxide benzoate stearate TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No;

NJ EHS: No; NY Part 597: No; PA HSL: No; SC TAP: No; WI

Air: No

112945-52-5 Silica, amorphous treated TSCA: No; CA PROP.65: No; CA TAC, Title 8: No; MA

Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No

CAS # Hazardous Components (Chemical Name) International Regulatory Lists

8042-47-5 White mineral oil Canadian DSL: Yes; Canadian NDSL: No; Mexico INSQ: Yes 64742-52-5 Aliphatic petroleum distillate Canadian DSL: Yes; Canadian NDSL: No; Mexico INSQ: Yes 1305-62-0 Hydrated lime Canadian DSL: Yes; Canadian NDSL: No; Mexico INSQ: Yes 1314-13-2 Zinc oxide Canadian DSL: Yes; Canadian NDSL: No; Mexico INSQ: Yes 14807-96-6 Talcum Canadian DSL: Yes; Canadian NDSL: No; Mexico INSQ: Yes 54326-11-3 Aluminum hydroxide benzoate stearate Canadian DSL: Yes; Canadian NDSL: No; Mexico INSQ: No 112945-52-5 Silica, amorphous treated Canadian DSL: Yes; Canadian NDSL: No; Mexico INSQ: Yes

16. OTHER INFORMATION

Revision Date: 05/05/2015

Additional Information About No data available.

This Product:

Company Policy or

Disclaimer:

Information presented herein is believed to be accurate and reliable to the best of our knowledge. However, we make no warranty or merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process. Users should make their own investigations to determine the suitability of the information for their particular purposes.