

Product Information Sheet



SPRAY-GLO FLUORESCENT SPRAY PAINT

An ultra high visibility spray paint for any project that requires a brilliant color. It has 400% greater visibility than regular paint. When topcoated with Seymour's UV resistant Clear coating, it provides exceptional outdoor durability. For best results use Seymour's Hi-Tech White Primer (#16-805) as a base coat. Two coats of Spray Glo are recommended followed by a UV resistant clear coating of Hi-Tech Gloss Clear Acrylic (#16-121).

Suggested Uses:

Hobby models Crafts House numbers Outdoor equipment Industrial Identification Safety Markings Warning Signs

Packaging:

Cans per case Shipping weight per case Container Label weight Shipping Classification Hazard Class 6 7 lbs. 16 fluid ounce can 12 ounces (340 grams) Consumer Commodity ORM-D, UN 1950 2.1

Properties:

Coverage Up to 15 square feet Cleanup Paint or lacquer thinner Flammability Flammable Flash point -4F Specific Gravity 0.80 Solids Content 26% MIR value 1.02, cannot exceed 1.30 HAPs content 0 Storage Temperature 40-90F Application Temperature 50-100F Heat Resistance 250F Resin System V.T. Alkyd Shelf life Guaranteed for 2 years

Dry Time*:

To touch 15 minutes

*At 72F, 50% humidity, 1.5 mil thickness

Curing/Recoat time is extended with multiple coats and excessively thick coats

Gloss*: Flat, <15

*as measured on a 60 degree gloss meter

Available Colors:

<u>Part #</u>	Description	UPC Code
16-1617	Fluorescent Orange	043281001144
16-1618	Fluorescent Red	043281001151
16-1619	Fluorescent Yellow	043281001168
16-1620	Fluorescent Green	043281001175
16-1621	Fluorescent Blue	043281001182

12-21-2019

Seymour of Sycamore 917 Crosby Avenue Sycamore, IL 60178 Phone:815-895-9101 or 800-435-4482Fax:815-895-8475 or 800-343-4258

www.seymourpaint.com