MATERIAL SAFETY DATA SHEET

SECTION I - PRODUCT IDENTIFICATION

SECTION 3 - PHYSICAL DATA

SUPPLIER'S NAME:

DATE ISSUED: 1/2012

MAGIC CLEANER

PRODUCT NAME: SPRAYZON

American Cleaning Solutions

DOT CLASSIFICATION: Corrosive

PRODUCT #: 31605

SUPPLIER'S ADDRESS: PO Box 1943 / 39-30 Review Avenue DOT SHIPPING NAME: Compound, Cleaning Liquid (contains Sodium Metasilicate)8, NA 1760,

Long Island City, NY 11101

PG II.

HAZARD RATING:

SECTION 4 - REACTIVITY DATA

PRODUCT TYPE: Cleaner

EMERGENCY PHONE: 800-535-5053

HEALTH: 2 FLAMMABILITY: 0

CHEMICAL FAMILY: Surfactant Blend

REACTIVITY: 1 PERSONAL PROTECTION: B

SECTION 2 - INGREDIENTS INFORMATION					
CHEMICAL NAME	CAS NO.	% / WT .	THRESHOLD LIMIT VALUE		
*2-BUTOXY ETHANOL	111-76-2	TO 6	25ppmTWA		
SODIUM METASILICATE	6834-92-0	TO 3	2mg/m3		
SODIUM PHOSPHATE, TRIBASIC	7758-29-4	TO 3	N/E		
NONIONIC SURFACTANT	9016-45-9	TO 3	N/E		
WATER	7732-18-5	TO 85	NONE		

^{*}An asterisk indicates the toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 and 40 CFR 372:

BOILING RANGE (F): 212-220° F	SPECIFIC GRAVITY: 1.04	STABILITY: Stable	
VAPOR PRESSURE: N/D	VAPOR DENSITY: Same as Water	HAZARDOUS POLYMERIZATION: Will Not 0	Occur
% VOLATILE : 90-94	pH : 12-13	INCOMPATIBILITY (MATERIALS TO AVOID)	: None
SOLUBILITY IN WATER: Complete	EVAPORATION RATE: N/A	HAZARDOUS DECOMPOSITION PRODUCTS	: Normal products of combustion
PHYSICAL DESCRIPTION: Purple Liquid, Sassafras Fragrance			
	•		
SECTION 5 - FIRE & EXP	LOSION HAZARD DATA	SECTION 6 - STORAGE & HANDL	ING INFORMATION
	LOSION HAZARD DATA	SECTION 6 - STORAGE & HANDL SPECIAL PRECAUTIONS: Keep out of reach of	
SECTION 5 - FIRE & EXP	LOSION HAZARD DATA	SPECIAL PRECAUTIONS: Keep out of reach of Use only in well vent	children. tilated area.
SECTION 5 - FIRE & EXP FLASH POINT: Exceeds 200° F	LOSION HAZARD DATA	SPECIAL PRECAUTIONS: Keep out of reach of Use only in well vent For institutional and	children. tilated area. industrial use only.
SECTION 5 - FIRE & EXP FLASH POINT: Exceeds 200° F FLAMMABILITY: Non-Flammable		SPECIAL PRECAUTIONS: Keep out of reach of Use only in well vent For institutional and For use by trained p	children. tilated area. industrial use only.

SECTION 7 - HEALTH HAZARD DATA		SECTION 8 - FIRST AID PROCEDURE
EYES: May cause irritation.	EXPOSURE LIMITS: N/E	EYES: Flush with running water for 15 minutes.
SKIN: May cause irritation.	CARCINOGENICITY: NTP: Not listed	SKIN: Wash off with soap and water.
INHALATION: May cause irritation to upper tract.	IARC: Not listed	INHALATION: Remove to fresh air.
INGESTION: May cause irritation of mucous membranes.	OSHA: Not regulated	INGESTION: Do not induce vomiting.

MEDICAL CONDITION AGGRAVATED BY EXPOSURE:	Dilink pienty of water.	
Persons with present skin disorder may be more susceptible to irritation.	If unconscious or in convulsion, take to hospital or physician.	

SECTION 9 - PRECAUTIONS FOR SAFE HANDLING	SECTION 10 - SPILL OR LEAK
RESPIRATORY PROTECTION: No special requirements.	SPILLAGE: Dike & contain spill, absorb the liquid.
PROTECTIVE GLOVES: Chemical resistant.	DISPOSAL: Scoop or shovel solid material into a suitable container for
VENTILATION: Good ventilation required.	recovery or disposal. Area may become slippery. Flush cleaned area with water.
EYE CONTACT: Goggles or Face Shield.	Dispose according to local, state and federal requirements.