MATERIAL SAFETY DATA SHEET

SECTION I - PRODUCT IDENTIFICATION

NON-AMMONIATED STRIPPER

PRODUCT #: 8826

PRODUCT TYPE: Alkaline Stripper

PRODUCT NAME: SUPER STRIP

CHEMICAL FAMILY: Surfactant Blend

SUPPLIER'S NAME:

American Cleaning Solutions

SUPPLIER'S ADDRESS:

PO Box 1943 / 39-30 Review Avenue

Long Island City, NY 11101

EMERGENCY PHONE: 800-535-5053

DATE ISSUED: 1/2012

DOT CLASSIFICATION: Corrosive

DOT SHIPPING NAME: Compound, Cleaning Liquid (contains Potassium Hydroxide) 8, NA 1760, PGII

HAZARD RATING:

HEALTH: 2 **FLAMMABILITY**: 0

REACTIVITY: 1 PERSONAL PROTECTION: B

SECTION 2 - INGREDIENTS INFORMATION				
CHEMICAL NAME	CAS NO.	% / WT .	THRESHOLD LIMIT VALUE	
*2-BUTOXYETHANOL	111-76-2	TO 5	25ppmTWA	
*POTASSIUM HYDROXIDE	1310-58-3	TO 4	2mg/m3	
*SODIUM SALT OF SILICIC ACID	6834-92-0	TO 5	25ppm	
*ETHANOLAMINE	141-43-5	TO 5	3ppmTWA	
WATER	7732-18-5	TO 81	NONE	

^{*}An asterisk indicates the toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 and 40 CFR 372:

All asterisk indicates the toxic chemicals subject to the reporting requirements of section 313 of the Emergency Flamming and Community Night-to-know Act of 1900 and 40 CFR 372.				
SECTION 3 - PHYSICAL DATA		SECTION 4 - REACTIVITY DATA		
BOILING RANGE (F): 212-220° F	Specific Gravity: 1.03	STABILITY: Stable		
VAPOR PRESSURE: N/D	VAPOR DENSITY: Same as Water	HAZARDOUS POLYMERIZATION: Will Not Occur		
% VOLATILE : 86-88	pH : 13	INCOMPATIBILITY (MATERIALS TO AVOID): Strong acids and oxidizers		
SOLUBILITY IN WATER: Complete	EVAPORATION RATE : N/A			
PHYSICAL DESCRIPTION: Yellowish / Green Liquid, Butyl Odor		HAZARDOUS DECOMPOSITION PRODUCTS: Normal products of combustion		
SECTION 5 - FIRE & EXP	LOSION HAZARD DATA	SECTION 6 - STORAGE & HANDLING INFORMATION		
FLASH POINT: Exceeds 200° F		SPECIAL PRECAUTIONS: Keep out of reach of children.		
FLAMMABILITY: Non-Flammable		Use only in well ventilated area.		
EXTINGUISHING MEDIA: Water, CO ₂		For institutional and industrial use only.		

SPECIAL FIRE FIGHTING PROCEDURES: Floor may be slippery

UNUSUAL AND EXPLOSION HAZARDS: None

SECTION 8 - FIRST AID PROCEDURE

Avoid freezing.

EXPOSURE LIMITS: N/E EYES: Flush with running water for 15 minutes. **EYES:** May cause severe irritation. **CARCINOGENICITY:** SKIN: May cause severe irritation. SKIN: Wash off with soap and water. NTP: Not listed **INHALATION:** May cause irritation to upper tract. IARC: Not listed

INGESTION: May cause irritation of mucous membranes. **OSHA:** Not regulated

SECTION 7 - HEALTH HAZARD DATA

MEDICAL CONDITION AGGRAVATED BY EXPOSURE:

Persons with present skin disorder may be more susceptible to irritation.

INHALATION: Remove to fresh air. **INGESTION:** Do not induce vomiting.

Drink plenty of water.

If unconscious or in convulsion, take to hospital or physician.

For use by trained personnel only.

Store and keep in closed container, in a cool place.

SECTION 9 - PRECAUTIONS FOR SAFE HANDLING

RESPIRATORY PROTECTION: No special requirements.

PROTECTIVE GLOVES: Chemical resistant.

VENTILATION: Good ventilation required.

EYE CONTACT: Goggles or Face Shield.

SECTION 10 - SPILL OR LEAK

SPILLAGE: Dike & contain spill, absorb the liquid.

DISPOSAL: Scoop or shovel solid material into a suitable container for

recovery or disposal. Area may become slippery.

Flush cleaned area with water.

Dispose according to local, state and federal requirements.