Formula #9205

# Strip Away

## Non-Ammoniated Stripper

Estripádo Sin Amoníaco

- Economical • Concentrated
- Fast Acting • Labor Saving

## Technical Data Sheet

### PRODUCT DESCRIPTION:
An economical formulation that blends butyl, alkali detergents and wetting agents for fast and effective removal of finish and wax from all types of floor surfaces.

### USES:
Strips off wax and finish with the use of a floor machine and a stripping pad. Can also be used as a cleaner and degreaser.

### ADVANTAGES:
Powerful fast acting, non-ammoniated formula, low material cost saves inventory dollars.

### SPECIFICATIONS:
Active Ingredients: 15%
pH: 13
Color: Blue
Solubility in Water: Complete
Odor: Mild Butyl
Flash Point: None
Viscosity: Water Thin
Weight per Gallon: 8.65 Lbs.

### PRODUCT/CONTAINER DISPOSAL:
Dispose of used/unwanted product according to state and local regulations. Offer container for recycling.

### SIZES AVAILABLE:
1 Gallon Bottle, 5 Gallon Pail, 30 & 55 Gallon Drums.

Formula #9205

Recyclable packaging

### PRODUCT USE / DILUTION RATE

| PRODUCT USE | DILUTION RATE |
|---|---|
| Light Build-Up | 12 oz. per gallon of hot water |
| Moderate Build-Up | 32 oz. per gallon of hot water |
| Heavy Build-Up | 64 oz. per gallon of hot water |

DILUTION MAY VARY BASED ON BUILD-UP OF OLD FINISH ON FLOOR SURFACE
PRODUCT DESIGNED FOR USE WITH HOT WATER

### DIRECTIONS FOR PRODUCT USE:
FOR BEST RESULTS, USE OF FLOOR MACHINE RECOMMENDED

1. Dilute concentrate per the chart above based on the amount of build-up.
2. Mop diluted solution liberally onto floor surface working in 5' x 5' sections.
3. Allow to stand 5-10 minutes. Keep area wet.
4. Scrub with a floor machine using a stripping pad, brush or mop.
5. Pick up solution with a wet-vac machine. Do not allow floor to dry.
6. Rinse floor thoroughly several times with clear water, amking sure all stripper solution is removed from the floor.
7. Apply first coat of finish or floor sealer in full uniform coat. Apply additional coats of floor finish as required.

**CAUTION:** Never allow solution to dry on floor. Always test solution on an inconspicuous area of floor to be stripped to check compatibility. Emulsified floor finish and wax are very slippery; keep area clear until surface is completely dry.

It is recommended that protective gloves and safety glasses be worn when using this and all cleaning products. Refer to MSDS for further safety information.

MANUFACTURED BY:

AMERICAN Cleaning Solutions
Division of American Wax Company, Inc.

39-30 Review Avenue
Long Island City, New York 11101
1-888 WAX PLUS • (718) 392-8080 Fax: (718) 482-9366
Visit us on the web! www.cleaning-solutions.com

MADE IN NYC