

# Crystal Shine Liquid Crystallization

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 04/15/2015

### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture  
Product name : Crystal Shine Liquid Crystallization  
Product code : 155-9398

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Floor coating

#### 1.3. Details of the supplier of the safety data sheet

American Cleaning Solutions  
39-30 Review Avenue  
Long Island City, NY 11101  
T (718) 392-8080

#### 1.4. Emergency telephone number

Emergency number : INFOTRAC: 800-535-5053

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### Classification (GHS-US)

Skin Irrit. 2 H315 - Causes skin irritation  
Eye Irrit. 2A H319 - Causes serious eye irritation  
Full text of H-phrases: see section 16

#### 2.2. Label elements

##### GHS-US labeling

Hazard pictograms (GHS-US) :



GHS07

Signal word (GHS-US) : Warning  
Hazard statements (GHS-US) : H315 - Causes skin irritation  
H319 - Causes serious eye irritation  
Precautionary statements (GHS-US) : P264 - Wash hands and forearms thoroughly after handling  
P280 - Wear protective gloves/eye protection/face protection  
P302+P352 - If on skin: Wash with plenty of soap and water  
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P321 - Specific treatment (see First aid measures on this label)  
P332+P313 - If skin irritation occurs: Get medical advice/attention  
P337+P313 - If eye irritation persists: Get medical advice/attention  
P362 - Take off contaminated clothing and wash it before reuse

#### 2.3. Other hazards

No additional information available

#### 2.4. Unknown acute toxicity (GHS US)

Not applicable

### SECTION 3: Composition/information on ingredients

#### 3.1. Substance

Not applicable

#### 3.2. Mixture

# Crystal Shine Liquid Crystallization

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	Classification (GHS-US)
Magnesium Hexafluorosilicate	(CAS No) 16949-65-8	5 - 10	Acute Tox. 3 (Oral), H301 Acute Tox. 4 (Inhalation:dust,mist), H332
Oxalic acid, dihydrate	(CAS No) 6153-56-6	1 - 5	Skin Corr. 1A, H314

Full text of H-phrases: see section 16

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : Allow victim to breathe fresh air. Allow the victim to rest.
- First-aid measures after skin contact : Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention. Specific treatment (see First aid measures on this label).
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after skin contact : Causes skin irritation.
- Symptoms/injuries after eye contact : Causes serious eye irritation.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

- Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.
- Unsuitable extinguishing media : Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

No additional information available

#### 5.3. Advice for firefighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

- Emergency procedures : Evacuate unnecessary personnel.

##### 6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.
- Emergency procedures : Ventilate area.

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

#### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

- Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor.
- Hygiene measures : Wash hands and forearms thoroughly after handling.

# Crystal Shine Liquid Crystallization

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Keep only in the original container in a cool, well ventilated place away from heat, hot surfaces, sparks, open flame and other ignition sources. No smoking. Keep container closed when not in use.
Incompatible products	: Strong bases. Strong acids.
Incompatible materials	: Sources of ignition. Direct sunlight.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Magnesium Hexafluorosilicate (16949-65-8)		
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	2.5 mg/m <sup>3</sup> (Fluorides, as F; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
Oxalic acid, dihydrate (6153-56-6)		
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	1 mg/m <sup>3</sup> (Oxalic acid; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
ACGIH	ACGIH STEL (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup> (Oxalic acid; USA; Short time value; TLV - Adopted Value)

### 8.2. Exposure controls

Personal protective equipment	: Avoid all unnecessary exposure.
Hand protection	: Wear protective gloves/eye protection/face protection protective gloves.
Eye protection	: Chemical goggles or safety glasses.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: Wear appropriate mask.
Other information	: Do not eat, drink or smoke during use.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: white
Odor	: mild
Odor threshold	: No data available
pH	: 1.5 - 2.5
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 212 - 220 °F
Flash point	: ≥ 200 °F
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: No data available
Relative density	: 1.06
Relative vapor density at 20 °C	: Same as water
Solubility	: Soluble in water. Water: Solubility in water of component(s) of the mixture : •: 49.84 g/100ml •: 14 g/100ml
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available

# Crystal Shine Liquid Crystallization

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Viscosity, dynamic : No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

Stable under normal conditions. Not established.

### 10.3. Possibility of hazardous reactions

Not established.

### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

### 10.5. Incompatible materials

Strong acids. Strong bases.

### 10.6. Hazardous decomposition products

Fume. Carbon monoxide. Carbon dioxide.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

Magnesium Hexafluorosilicate (16949-65-8)	
LD50 oral rat	291 mg/kg body weight (Rat; Equivalent or similar to OECD 401; Experimental value)
LC50 inhalation rat (mg/l)	3.6 mg/l/4h (Rat; Experimental value)
ATE US (oral)	291.000 mg/kg body weight
ATE US (vapors)	3.600 mg/l/4h
ATE US (dust, mist)	3.600 mg/l/4h

Skin corrosion/irritation : Causes skin irritation.  
pH: 1.5 - 2.5

Serious eye damage/irritation : Causes serious eye irritation.  
pH: 1.5 - 2.5

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated exposure) : Not classified

Aspiration hazard : Not classified

Potential Adverse human health effects and symptoms : Based on available data, the classification criteria are not met.

Symptoms/injuries after skin contact : Causes skin irritation.

Symptoms/injuries after eye contact : Causes serious eye irritation.

## SECTION 12: Ecological information

### 12.1. Toxicity

Magnesium Hexafluorosilicate (16949-65-8)	
LC50 fish 1	> 100 mg/l (LC50; OECD 203: Fish, Acute Toxicity Test; 96 h; Danio rerio; Static system; Fresh water; Experimental value)

# Crystal Shine Liquid Crystallization

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Magnesium Hexafluorosilicate (16949-65-8)	
EC50 Daphnia 1	70.7 mg/l (EC50; OECD 202: Daphnia sp. Acute Immobilisation Test; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)
Threshold limit algae 1	34.2-34.7, EC50; OECD 201: Alga, Growth Inhibition Test; 72 h; Pseudokirchneriella subcapitata; Static system; Fresh water; Experimental value
Oxalic acid, dihydrate (6153-56-6)	
LC50 fish 1	34.1 mg/l (LC50; 96 h)
EC50 Daphnia 1	137 mg/l (EC50; 48 h)

### 12.2. Persistence and degradability

Crystal Shine Liquid Crystallization	
Persistence and degradability	Not established.
Magnesium Hexafluorosilicate (16949-65-8)	
Persistence and degradability	Biodegradability: not applicable. No (test) data on mobility of the substance available.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
Oxalic acid, dihydrate (6153-56-6)	
Persistence and degradability	Readily biodegradable in water. Readily biodegradable in water in anaerobic conditions. Photolysis in water. Biodegradable in the soil. Photolysis in the air.

### 12.3. Bioaccumulative potential

Crystal Shine Liquid Crystallization	
Bioaccumulative potential	Not established.
Magnesium Hexafluorosilicate (16949-65-8)	
Bioaccumulative potential	No bioaccumulation data available.
Oxalic acid, dihydrate (6153-56-6)	
Log Pow	-1.74 (Estimated value)
Bioaccumulative potential	Bioaccumulation: not applicable.

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

Effect on the global warming	: No known ecological damage caused by this product.
Other information	: Avoid release to the environment.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials	: Avoid release to the environment.

## SECTION 14: Transport information

### Department of Transportation (DOT)

In accordance with DOT	
Transport document description	: NA1760 Compounds, cleaning liquid (Contains Magnesium Silicofluoride), 8, III
UN-No.(DOT)	: NA1760
Proper Shipping Name (DOT)	: Compounds, cleaning liquid Contains Magnesium Silicofluoride
Transport hazard class(es) (DOT)	: 8 - Class 8 - Corrosive material 49 CFR 173.136

# Crystal Shine Liquid Crystallization

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard labels (DOT)

: 8 - Corrosive



Packing group (DOT)

: III - Minor Danger

DOT Packaging Non Bulk (49 CFR 173.xxx)

: 202

DOT Packaging Bulk (49 CFR 173.xxx)

: 242

DOT Symbols

: D - Proper shipping name for domestic use only, or to and from Canada, G - Identifies PSN requiring a technical name

DOT Special Provisions (49 CFR 172.102)

: B2 - MC 300, MC 301, MC 302, MC 303, MC 305, and MC 306 and DOT 406 cargo tanks are not authorized.

IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.

N37 - This material may be shipped in an integrally-lined fiber drum (1G) which meets the general packaging requirements of subpart B of part 173 of this subchapter, the requirements of part 178 of this subchapter at the packing group assigned for the material and to any other special provisions of column 7 of the 172.101 table.

T11 - 6 178.274(d)(2) Normal..... 178.275(d)(3)

TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.

TP27 - A portable tank having a minimum test pressure of 4 bar (400 kPa) may be used provided the calculated test pressure is 4 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 154

DOT Quantity Limitations Passenger aircraft/rail : 1 L  
(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 30 L  
CFR 175.75)

DOT Vessel Stowage Location

: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

DOT Vessel Stowage Other

: 40 - Stow "clear of living quarters"

Other information

: No supplementary information available.

### TDG

No additional information available

### Transport by sea

No additional information available

### Air transport

No additional information available

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

#### Magnesium Hexafluorosilicate (16949-65-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### Oxalic acid, dihydrate (6153-56-6)

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

# Crystal Shine Liquid Crystallization

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 15.2. International regulations

#### CANADA

No additional information available

#### EU-Regulations

No additional information available

#### National regulations

No additional information available

### 15.3. US State regulations

No additional information available

## SECTION 16: Other information

Revision date : 04/15/2015

Other information : None.

Full text of H-phrases:

Acute Tox. 3 (Oral)	Acute toxicity (oral) Category 3
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Skin Corr. 1A	Skin corrosion/irritation Category 1A
Skin Irrit. 2	Skin corrosion/irritation Category 2
H301	Toxic if swallowed
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled

HMIS III Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur  
Flammability : 0 Minimal Hazard - Materials that will not burn  
Physical : 1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high temperatures and pressures. Materials may react non-violently with water or undergo hazardous polymerization in the absence of inhibitors.  
Personal Protection : B  
B - Safety glasses, Gloves

SDS US (GHS HazCom 2012)

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*