

## POWER TECH®

## 25ft 12/3 SJTW Triple Tap GFCI Extension Cords



Power Tech® Triple Tap GFCI Extension Cords offer extra shock protection by incorporating GFCI units rated at 20A instead the standard 15A units commonly found in the market. Our patented solid state GFCI unit provides protection from electrical shock by interrupting the circuit to a load when a fault current of 6mA or higher is detected. It offers neutral protection, ground neutral protection, and built in surge protection for cords, power tools, small appliances, electronics, and more when they are plugged into the GFCI adapter.

## **FEATURES**

- The GFCI has a manual reset feature that ensures that equipment won't have accidental restarts without fixing the issue, providing additional protection for you, your tools and your equipment
- Class A GFCI unit with a 4-6mA trip level
- · Power On indicator (Red means on)
- Cords are manufactured to 12/3 AWG (American Wire Gauge) specifications
- Each of the three conductors contain 65 strands of 30 AWG 100% copper wire
- All copper is soft drawn & annealed for maximum flexibility under full load
- Our Century® coldweather PVC insulation and jacket guarantees working flexibility in temperatures down to -40°F
- SJTW outside jacket is rated at 300 volts
- We use heavy duty molded on 15A-125V NEMA 5-15 plugs & connectors that will not to pull away from the cord body
- Triple Tap connector provides (3) additional power outlets when needed
- · Cord Jacket color: Blue
- Lengths: 25ft, 50ft & 100ft
- Surge Suppression: 13 Joules
- UL Listed and CSA Approved for Canada

WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Part number **D18030025** 

Length 25'

Description

12/3 SJTW Triple Tap Extension Cord with Inline GFCI

Product line

Power Tech® GFCI Extension Cord

Colc

Blue

Gauge/Conductors

12/3

Wire type

SJTW

Certifications

CSA, UL, OSHA

Electrical ratings 15A, 125V, 1875W

Product packaging

**Cuff wrapper** 

Unit dimensions D x W x H (inches)

12.0 x 12.0 x 2.3

Unit weight (lbs)

6.5

Master carton type

Plain corrugated

Master carton dimensions D x W x H

12.5 x 23.0 x 7.0

Master carton weight (lbs)

40

Master carton case quantity

6

Master carton cube (cu. ft.) **1.2** 

- --

UPC

661899 116076

## Custom Print Available, Absolutely Free! Allow 7 Extra Days For Delivery.

We'll print your customer's name and telephone number every 12 inches down the entire length of the cord.

Printed cords discourage jobsite theft and provide instant advertising and company recognition which will

promote more business.