




safewaze.com | (P) 704-262-7893 | (F) 704-262-9051
322 Industrial Court, Concord, NC 28025

TECHNICAL DATA SHEET

FS-EX2530-G-SL

30' Cable Retractable w/ Locking Snap Hook



**Subdued
Edge
Rated**



Features and Benefits

Safewaze™ retractable lifelines are designed to be used as a single-person fall protection device. The FS-EX2530-G-SL features a rugged and durable housing, swivel fall indicator hook, heavy duty rubber shock protector and pull grip, a ceramic cable entry point with brush to reduce internal contamination, and a unique braking system that eases shock in the event of a fall.

Length of Cable 30 ft (9.14 m)

Weight of Unit 11.00 lbs (4.98 kg)

Materials High-strength polymer housing
3/16 in (4.76 mm) Galvanized steel cable
Forged steel snap hook

Hook Ratings 5,000 lbs (2267.96 kg) Tensile Strength
3,600 lbs (1632 kg) Gate Rated

Maximum Arresting Force <1,800 lbs (816.47 kg)

Maximum Arrest Distance <54 in (1371.6 mm)

Maximum Working Load ANSI 130-310 lbs (58.97-140.61 kg)
OSHA up to 420 lbs (190.51 kg)

Cable Tensile Strength 3,700 lbs (1678.29 kg)

Applicable Standards Meets OSHA 1926.502 - ANSI Z359.14 - ANSI A10.32