TECHNICAL DATA SHEET



<u>safewaze.com</u> | (P) 704-262-7893 | (F) 704-262-9051 322 Industrial Court. Concord. NC 28025

FS-FSP1220-SS 20' CLASS A SS Cable Retractable w/ Swivel Fall Indicator Hook



Features and Benefits Safewaze™ retractable lifelines are designed to be used as a

single-person fall protection device. The FS-FSP1220-SS features a mobility-enhancing swivel-top, a rugged and durable housing, and a unique braking system that eases shock in the event of a fall.

Length of Cable 20 ft (6.09 m)

Weight of Unit 7.8 lbs (3.54 kg)

Materials High-strength polymer housing

0.19 in (4.82 mm) Stainless steel cable

Forged steel snap hook

Steel carabiner

Hook Ratings 5,000 lbs (2267.96 kg) Tensile Strength

3,600 lbs (1632 kg) Gate Rated

Arresting Force Max Force <1,800 lbs (816.47 kg); Avg Force <1,350 lbs (612.35 kg)

Maximum Arrest Distance <24 in (609.6 mm)

Maximum Working Load ANSI 130-310 lbs (58.97-140.61 kg)

OSHA up to 420 lbs (190.51 kg)

Cable Tensile Strength 3,700 lbs (1678.29 kg)

Applicable Standards Meets OSHA 1926.502 - ANSI Z359.14-2014 - ANSI A10.32