

Date Prepared: 02/15/2014

MSDS No: 11790469_PL34507

Date-Revised: 09/20/2017

Revision No: 6

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT DESCRIPTION: 40107 SOLUTION 12 GREEN 50ML

MANUFACTURER

MRO Solutions L.L.C. 5645 West Howard Street Niles, IL 60714

Service Number: (847) 588-2480

24 HR. EMERGENCY TELEPHONE NUMBERS

MRO Solutions – For Chemical Emergency/Information (847) 588-2480

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS

Health:

Skin Irritation, Category 2
Eye Irritation, Category 2
Target Organ Toxicity (Single exposure), Category 3

GHS LABEL ELEMENTS

Note: If this product is a consumer product it is labeled in accordance with the Consumer Product Safety Commission regulations and not OSHA regulations. The requirements for the labeling of consumer products take precedence over OSHA labeling so the actual product label will not contain the OSHA label elements shown below on this SDS.



SIGNAL WORD: WARNING HAZARD STATEMENTS

H315: Causes skin irritation.

H319: Causes serious eye irritation. H335: May cause respiratory irritation.

PRECAUTIONARY STATEMENT(S)

Prevention:

P271: Use only outdoors or in a well-ventilated area.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P260: Do not breathe dust/fume/gas/mist/vapours/spray.

P362: Take off contaminated clothing.

Response:

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.



Date Prepared: 02/15/2014

MSDS No: 11790469_PL34507

Date-Revised: 09/20/2017

Revision No: 6

P302+P352: IF ON SKIN: Wash with plenty of water/...

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312: Call a POISON CENTER/doctor/...if you feel unwell.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

Storage:

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P405: Store locked up.

Disposal:

7944L5O1: Dispose of in a manner consistent with federal, state, and local regulations.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS
Polyethylene Glycol Dimethacrylate	≥ 85	25852-47-5
Cumene Hydroperoxide	1 - 3	80-15-9

4. FIRST AID MEASURES

EYES: Immediately flush eyes with large quantities of water for several minutes, while holding eyelids apart. Remove contact lenses if easy to do so. Continue rinsing. Get medical attention if irritation or bonding occurs.

SKIN: Immediately flush skin with plenty of water. Remove clothing. Get medical attention immediately. Wash clothing separately before reuse.

INGESTION: If swallowed, do not induce vomiting. Keep individual calm. Get medical attention and show container label.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

EYES: Causes eye irritation.

SKIN: Causes skin irritation. Allergic reactions are possible.

SKIN ABSORPTION: Remove contaminated clothing and wash affected areas with soap and water. Prolonged or repeated contact can cause dermatitis in sensitive individuals. Contact a physician if irritation persists.

INGESTION: Slight to very low toxicity.

INHALATION: Prolonged or excessive inhalation may cause respiratory tract irritation.

ACUTE EFFECTS: Irritating to skin. May cause allergic skin reaction with prolonged contact.

CHRONIC EFFECTS: Frequent or prolonged contact may irritate the skin and cause a skin rash (dermatitis).

5. FIRE FIGHTING MEASURES

FLAMMABLE CLASS: Not Flammable

EXTINGUISHING MEDIA: Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.

HAZARDOUS COMBUSTION PRODUCTS: Carbon Dioxide, Carbon Monoxide and other toxic or irritating compounds may form when heated to decomposition.

EXPLOSION HAZARDS: This material is a water pollutant and should be prevented from contaminating soil or from entering



Date Prepared: 02/15/2014

MSDS No: 11790469_PL34507

Date-Revised: 09/20/2017

Revision No: 6

sewage and drainage systems and bodies of water.

FIRE FIGHTING PROCEDURES: Firefighters should wear self-contained breathing apparatus and protective clothing.

FIRE FIGHTING EQUIPMENT: As in any fire, wear self-contained breathing apparatus pressure-demand, (MSHA/NIOSH approved or equivalent) and full protective gear.

FIRE EXPLOSION: This material is a water pollutant and should be prevented from contaminating soil or from entering sewage and drainage systems and bodies of water.

SENSITIVE TO STATIC DISCHARGE: This material is a water pollutant and should be prevented from contaminating soil or from entering sewage and drainage systems and bodies of water.

SENSITIVITY TO IMPACT: This material is a water pollutant and should be prevented from contaminating soil or from entering sewage and drainage systems and bodies of water.

HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of carbon and nitrogen.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Absorb liquid and place in sealed container for disposal.

LARGE SPILL: This material is a water pollutant and should be prevented from contaminating soil or from entering sewage and drainage systems and bodies of water.

ENVIRONMENTAL PRECAUTIONS

WATER SPILL: Avoid runoff into storm sewers and ditches which lead to waterways.

LAND SPILL: This material is a water pollutant and should be prevented from contaminating soil or from entering sewage and drainage systems and bodies of water.

AIR SPILL: This material is a water pollutant and should be prevented from contaminating soil or from entering sewage and drainage systems and bodies of water.

GENERAL PROCEDURES: Polymerize with water. Increase ventilation to area. Solid material may be scraped from surface. **SPECIAL PROTECTIVE EQUIPMENT:** Use plastic/rubber gloves, chemical splash goggles or safety glasses with side shields.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Use with adequate ventilation. Avoid contact with eyes, skin and clothing.

HANDLING: Avoid contact with skin and eyes. Wash thoroughly after handling.

STORAGE: Store in a cool place in original container and protect from sunlight. Keep away from sources of ignition.

STORAGE TEMPERATURE: Suggested storage conditions: Less than 77F/25C. Protect from freezing.

LOADING TEMPERATURE: Not Established

LOADING/UNLOADING VISCOSITY: Not Established

STORAGE PRESSURE: Not Established

ELECTROSTATIC ACCUMULATION HAZARD: No data available

8. EXPOSURE CONTROLS / PERSONAL PROTECTION



Date Prepared: 02/15/2014

MSDS No: 11790469_PL34507

Date-Revised: 09/20/2017

Revision No: 6

EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)				
	EXPOSURE LIMITS			
Chemical Name	Туре		ppm	mg/m³
Cumene Hydroperoxide	OSHA PEL	TWA	50	245

ENGINEERING CONTROLS: Good general ventilation should be sufficient to control airborne levels.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact, wear splash-proof goggles.

SKIN: Vinyl or rubber gloves.

RESPIRATORY: This material does not have established exposure limits. Wear a positive pressure air-supplied respirator in situations where there may be potential for airborne exposure.

PROTECTIVE CLOTHING: Not Applicable.

WORK HYGIENIC PRACTICES: Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

ODOR: Mild odor

ODOR THRESHOLD: No data available

APPEARANCE: Green liquid.

COLOR: Green

pH: No data available

PERCENT VOLATILE: No data available

FLASHPOINT AND METHOD: No data available

AUTOIGNITION TEMPERATURE: No data available

VAPOR PRESSURE: No data available
VAPOR DENSITY: No data available
BOILING POINT: No data available
FREEZING POINT: No data available
MELTING POINT: No data available
POUR POINT: No data available

THERMAL DECOMPOSITION: No data available SOLUBILITY IN WATER: No data available

EVAPORATION RATE: No data available

DENSITY: No data available

SPECIFIC GRAVITY: No data available

VISCOSITY: No data available



Date Prepared: 02/15/2014

MSDS No: 11790469_PL34507

Date-Revised: 09/20/2017

Revision No: 6

MOLECULAR WEIGHT: No data available

(VOC): No data available

10. STABILITY AND REACTIVITY

REACTIVITY: Yes

HAZARDOUS POLYMERIZATION: No

STABILITY: Stable

CONDITIONS TO AVOID: Avoid temperatures exceeding 100F/38C and incompatible materials.

POSSIBILITY OF HAZARDOUS REACTIONS: Hazardous reactions are possible when exposed to incompatible materials such

as nitrates, chlorine, ammonia, strong oxidizers, alkalis, and acids

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon Dioxide, Carbon Monoxide and other toxic or irritating compounds may

form when heated to decomposition.

INCOMPATIBLE MATERIALS: Strong acids and alkalis, reactive metals and strong oxidizing agents.

COMMENTS: REACTIVITY: product may react if exposed to amines, inert gases, metallic salts, heat sources or oxidizers.

11. TOXICOLOGICAL INFORMATION

ACUTE TOXICITY

Chemical Name	ORAL LD ₅₀ (rat)	DERMAL LD ₅₀ (rabbit)	INHALATION LC ₅₀ (rat)
Polyethylene Glycol Dimethacrylate	> 2000 mg/kg		
Cumene Hydroperoxide	382 mg/kg (rat)	133 mg/kg (rabbit)	220 ppm per 4 hr (rat)

RESPIRATORY OR SKIN SENSITISATION: May cause sensitization by skin contact.

CARCINOGENICITY

IARC: Prevent contamination of soil, drains and surface waters. Dike and contain material. Soak up residue with absorbent (clay, sand) materials and dispose of properly.

NTP: Prevent contamination of soil, drains and surface waters. Dike and contain material. Soak up residue with absorbent (clay, sand) materials and dispose of properly.

OSHA: Prevent contamination of soil, drains and surface waters. Dike and contain material. Soak up residue with absorbent (clay, sand) materials and dispose of properly.

GENERAL COMMENTS: Prevent contamination of soil, drains and surface waters. Dike and contain material. Soak up residue with absorbent (clay, sand) materials and dispose of properly.

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: No known ecological affects of cured product.

ECOTOXICOLOGICAL INFORMATION: Prevent contamination of soil, drains and surface waters. Dike and contain material. Soak up residue with absorbent (clay, sand) materials and dispose of properly.

BIOACCUMULATION/ACCUMULATION: Prevent contamination of soil, drains and surface waters. Dike and contain material. Soak up residue with absorbent (clay, sand) materials and dispose of properly.

DISTRIBUTION: Prevent contamination of soil, drains and surface waters. Dike and contain material. Soak up residue with absorbent (clay, sand) materials and dispose of properly.



Date Prepared: 02/15/2014

MSDS No: 11790469_PL34507

Date-Revised: 09/20/2017

Revision No: 6

AQUATIC TOXICITY (ACUTE): Prevent contamination of soil, drains and surface waters. Dike and contain material. Soak up residue with absorbent (clay, sand) materials and dispose of properly.

CHEMICAL FATE INFORMATION: Prevent contamination of soil, drains and surface waters. Dike and contain material. Soak up residue with absorbent (clay, sand) materials and dispose of properly.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Dispose of following all Local Authority requirements for disposal.

14. TRANSPORT INFORMATION

PRODUCT DISPOSAL: Dispose of following all Local Authority requirements for disposal. **EMPTY CONTAINER:** Dispose of following all Local Authority requirements for disposal.

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: Not restricted

ROAD AND RAIL (ADR/RID)

PROPER SHIPPING NAME: Not restricted

AIR (ICAO/IATA)

SHIPPING NAME: Not restricted

VESSEL (IMO/IMDG)

SHIPPING NAME: Not restricted

CANADA TRANSPORT OF DANGEROUS GOODS

SHIPPING NAME: Not restricted

15. REGULATORY INFORMATION

UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

311/312 HAZARD CATEGORIES: Immediate (acute) health and Delayed (chronic) health hazards.

FIRE: No PRESSURE GENERATING: No REACTIVITY: No ACUTE: Yes CHRONIC: Yes

313 REPORTABLE INGREDIENTS: Section 313: Cumene hydroperoxide (CAS 80-15-9), less than 3%.

EPCRA SECTION 313 SUPPLIER NOTIFICATION

Chemical Name	Wt.%	CAS
Cumene Hydroperoxide	1 - 3	80-15-9

CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)

CERCLA REGULATORY: Contains Cumene hydroperoxide (CAS 80-15-9), less than 3%.

Chemical Name	Wt.%	CERCLA RQ
Cumene Hydroperoxide	1 - 3	10

TSCA (TOXIC SUBSTANCE CONTROL ACT)



Date Prepared: 02/15/2014

MSDS No: 11790469_PL34507

Date-Revised: 09/20/2017

Revision No: 6

Chemical Name	CAS
Polyethylene Glycol Dimethacrylate	25852-47-5
Cumene Hydroperoxide	80-15-9

TSCA STATUS: All components are listed on or are exempt from listing on the Toxic Substances Control Act.

CALIFORNIA PROPOSITION 65: WARNING: This product can expose you to chemicals including Cumene, which is known to the State of California to cause cancer, and Ethylene glycol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

CANADA

WHMIS CLASS: D2B - Toxic (Irritant)


16. OTHER INFORMATION

APPROVED BY: Regulatory Affairs Manager

PREPARED BY: Regulatory Affairs Manager Date-Revised: 09/20/2017

REVISION SUMMARY: This MSDS replaces the 01/27/2015 MSDS. Revised: Section 1: APPROVED BY, MSDS No, PREPARED BY, TITLE. Section 2: . Section 3: Wt.%. Section 6: GENERAL PROCEDURES, . Section 9: AUTOIGNITION TEMPERATURE, BOILING POINT, COLOR, DENSITY, EVAPORATION RATE, FLAMMABLE LIMITS, FLASHPOINT AND METHOD, FREEZING POINT, MELTING POINT, MOLECULAR WEIGHT, PERCENT VOLATILE, pH, SOLUBILITY IN WATER, SPECIFIC GRAVITY, VAPOR PRESSURE, VISCOSITY, VISCOSITY #1, (VOC), . Section 11: ACUTE, SKIN CORROSION/IRRITATION. Section 13: EMPTY CONTAINER, PRODUCT DISPOSAL. Section 15: CALIFORNIA PROPOSITION 65.

HMIS RATING		
HEALTH	2	
FLAMMABILITY	1	
PHYSICAL HAZARD	1	
PERSONAL PROTECTION	В	



HMIS RATINGS NOTES: Safety glasses and gloves are recommended for usage.

MANUFACTURER DISCLAIMER:

To the best of our knowledge, the information contained herein is accurate. However, MRO Solutions does not assume any liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.