TECHNICAL DATA SHEET



<u>safewaze.com</u> | (P) 704-262-7893 | (F) 704-262-9051 322 Industrial Court, Concord, NC 28025

SW-8008-10-ALU 10' CLASS A Cable Retractable



Features and Benefits Safewaze™ retractable lifelines are designed to be used as a single-

person fall protection device. The SW-8008-10-ALU features a mobility-enhancing swivel-top, rugged and durable housing, and a unique braking system that eases shock in the event of a fall.

Length of Cable 10 ft (3.05 m)

Weight of Unit 4.15 lbs (1.88 kg)

Materials High-strength polymer housing

0.19 in (4.82 mm) Galvanized steel cable

Aluminum snap hook

Hook Ratings 5,000 lbs (2267.96 kg) Tensile Strength

3,600 lbs (1632 kg) Gate Rated

Arresting Force Max Force<1,800 lbs (816.47 kg); Avg Force <1,350 lbs (612.35 kg)

Maximum Arrest Distance Arresting distance <24 in (609.60 mm)

Maximum Working Load 420 lbs (190.51 kg)

Cable Tensile Strength 3,700 lbs (1678.29 kg)

Applicable Standards Meets OSHA 1926.502 - ANSI Z359.14 - ANSI A10.32