



[safewaze.com](http://safewaze.com) | (P) 704-262-7893 | (F) 704-262-9051  
322 Industrial Court, Concord, NC 28025

## TECHNICAL DATA SHEET

### FS-EX210

Easy Slider I-Beam Anchor



<b>Description</b>	Adjustable I-beam anchor
<b>Beam Flange Width Range</b>	3.5 in (88.9 mm) - 14 in (255.6 mm)
<b>Beam Flange Thickness</b>	Up to 1.25 in (31.75 mm)
<b>Weight</b>	3.4 lbs (1.54 kg)
<b>Maximum Capacity</b>	One worker 310 lbs (140.6 kg)
<b>Materials &amp; Components</b>	Aluminum crossbar Stainless steel D-ring bracket Clamps - Bronze Zinc-plated steel D-ring, spring and hardware
<b>Static Tensile Strength</b>	5,000 lbs (22kN)
<b>Applicable Standards</b>	Meets OSHA 1926.502 - OSHA 1910.66 ANSI Z359.18 (Type T) - ANSI Z359.7-2011

**\*Anchorages used for attachment of personal fall arrest equipment shall be independent of any anchorage being used to support or suspend platforms and be capable of supporting at least 5,000 (22.2kN) pounds per employee attached.**