

**NEW**  
Solid  
Carbide  
Bits

# Carbide Drill Bits

Power • Precision • Dependability

Powers is a proud member of:



**Powers**  
FASTENERS



A domestic  
company  
manufactured  
in Brocton, NY

# Carbide Drill Bits



**NEW**

## Fat-Head™ Bits

### PRODUCT DESCRIPTION

The Powers Fat-Head™ combines an intelligent, innovative geometry with uncompromising quality in its detail. This is reflected in prolonged durability, precision drilled holes and exceptional low vibration - even when the going gets tough. A premium tool for anyone who has to drill into reinforced concrete or natural stone.

### FEATURES AND BENEFITS

- 4x 90° head symmetry prevents sticking when rebar is hit, ensures precision drilled holes and provides low vibration for increased rotational stability.
- Centering tip for easy spot drilling with pinpoint accuracy.
- Short and wide dust entrances quickly channel the drilling dust from the drill bit head into the flute for less wear and heat build up.
- One piece embedded carbide element with four chamfered edges for optimal drilling performance in reinforced concrete, low vibration with no sticking and improved bit life and break resistance.
- 4-Fluted spiral geometry distributes work load equally for low and uniform wear while the high volume flute quickly removes drilling dust. The optimized flute core strength ensure impact durability and increased rotational stability for less vibration.

## Fat-Head™ Bits

Use In: Rotary hammer with SDS chuck or SDS adapter  
Size Range: 3/16" x 4-1/4" to 9/16" x 18"

Cat. No.	Size	Usable Length	Std. Tube
0701	3/16" x 4-1/4"	2"	1
0703	3/16" x 6-1/4"	4"	1
0705	3/16" x 8-1/4"	6"	1
0707	3/16" x 10-1/4"	8"	1
0709	3/16" x 12-1/4"	10"	1
0711	1/4" x 4-1/4"	2"	1
0713	1/4" x 6-1/4"	4"	1
0715	1/4" x 8-1/4"	6"	1
0717	1/4" x 10-1/4"	8"	1
0719	1/4" x 12-1/4"	10"	1
0721	5/16" x 6-1/4"	4"	1
0723	5/16" x 12-1/4"	10"	1
0725	5/16" x 18"	16"	1
0727	3/8" x 6-1/4"	4"	1
0729	3/8" x 12-1/4"	10"	1
0731	3/8" x 18"	16"	1
0733	7/16" x 6-1/4"	4"	1
0735	7/16" x 12-1/4"	10"	1
0737	7/16" x 18"	16"	1
0739	1/2" x 6-1/4"	4"	1
0741	1/2" x 12-1/4"	10"	1
0743	1/2" x 18"	16"	1
0745	9/16" x 6-1/4"	4"	1
0747	9/16" x 12-1/4"	10"	1
0749	9/16" x 18"	16"	1
0751	5 Piece Drill Set Kit includes 3/16", 1/4", 5/16", 3/8" & 1/2" diameter bits (all 6" overall)		1

4x 90° head symmetry

Centering Tip

Short & Wide Dust Entrances

Chamfered Edges

# Carbide Drill Bits

## SDS-Plus / S-4 Plus SDS

Use In: Rotary hammer with SDS chuck or SDS adapter  
Size Range: 5/32" x 6" to 1" x 18"

Bits conform with ANSI Standard B212.15 and can be used to drill in concrete, block, brick, & soft stone.

Cat. No.	Size	Usable Length	Std. Pouch
0302	5/32" x 6"	4"	1
0304	3/16" x 4"	2"	1
0306	3/16" x 6"	4"	1
0308	3/16" x 8"	6"	1
0310	3/16" x 10"	8"	1
0312	3/16" x 12"	10"	1
0314	3/16" x 14"	12"	1
0316	7/32" x 8"	6"	1
0317	7/32" x 10"	8"	1
0318	7/32" x 12"	10"	1
0319	7/32" x 16"	14"	1
0320	1/4" x 4"	2"	1
0321	1/4" x 6"	4"	1
0322	1/4" x 8"	6"	1
0323	1/4" x 11"	9"	1
0324	1/4" x 14"	12"	1
0325	1/4" x 16"	14"	1
0327	1/4" x 20"	18"	1
0329	5/16" x 6"	4"	1
0331	5/16" x 12"	10"	1
0333	3/8" x 6"	4"	1
0334	3/8" x 10"	8"	1
0336	3/8" x 12"	10"	1
0338	3/8" x 18"	16"	1
0339	3/8" x 24"	22"	1
0341	7/16" x 6"	4"	1
0343	7/16" x 12"	10"	1
0346	1/2" x 6"	4"	1
0348	1/2" x 10"	8"	1
0349	1/2" x 12"	10"	1
0351	1/2" x 18"	16"	1
0352	1/2" x 24"	22"	1
0354	9/16" x 6"	4"	1
0355	9/16" x 12"	8"	1
0359	5/8" x 8"	6"	1
0361	5/8" x 12"	10"	1
0362	5/8" x 18"	16"	1
0364	11/16" x 8"	6"	1
0365	11/16" x 12"	10"	1
0368	3/4" x 8"	6"	1
0370	3/4" x 12"	10"	1
0371	3/4" x 18"	16"	1
0373	27/32" x 8"	6"	1
0375	7/8" x 8"	6"	1
0376	7/8" x 12"	10"	1
0377	7/8" x 18"	16"	1
0379	1" x 8"	6"	1
0380	1" x 10"	8"	1
0381	1" x 12"	10"	1
0382	1" x 18"	16"	1
0394†	Spline to SDS Adapter-	1	
0396†	SDS Max Adapter	-	1

† Use of SDS-Plus® drill bit in larger rotary hammers with an adapter will reduce bit life.

## Special Application Bit for 3/8" Pipe SPIKE®

For use in hard aggregate concrete. Job site tests required.

Cat. No.	Size	Usable Length	Std. Pouch
0390*	7mm x 4" Pipe SPIKE® Bit	2"	1

\* Discontinued item once current stock exhausted.

## SDS-Plus® / S-4 Plus™ SDS Carbide Drill Bit Bulk Packs

Cat. No.	Size	Usable Length	Bits Per Pack
0662	5/32" x 6"	4"	25
0664	3/16" x 4"	2"	25
0666	3/16" x 6"	4"	25
0668	3/16" x 8"	6"	25
0670	3/16" x 10"	8"	25
0675	7/32" x 6"	4"	25
0676	7/32" x 8"	6"	25
0677	7/32" x 10"	8"	25
0680	1/4" x 4"	2"	25
0681	1/4" x 6"	4"	25
0682	1/4" x 8"	6"	25
0683	1/4" x 11"	9"	25
0689	5/16" x 6"	4"	25
0693	3/8" x 6"	4"	25
0696	1/2" x 6"	4"	15
0697	5/8" x 8"	6"	15

## SDS-Plus® 1/2" Accu-Bit™ for 3/8" DropIn

Cat. No.	Size	Usable Length	Bits Per Pack
0397	SDS-Plus® 1/2" Concrete Accu-Bit™ for 3/8" Standard DropIn	1	10

## SDS-Plus® 3/8" Accu-Bit™ for Mini DropIn

Cat. No.	Size	Usable Length	Bits Per Pack
0398	SDS-Plus® 3/8" Concrete Accu-Bit™ for Mini DropIn	1	10



SDS-Plus



Accu-Bit™



# Carbide Drill Bits

## Quatro

### Quatro Head SDS-Plus Carbide Drill Bits

Designed to reduce vibration and noise. These bits produce rounder and more accurately located anchor holes.

Cat. No.	Size	Usable Length	Std. Pouch
7086*	3/4" x 18"	16"	1
7094	1-1/8" x 18"	16"	1
7095	1-1/4" x 18"	16"	1

\* Discontinued item once current stock exhausted.

### Industrial Grade Bits (Value Paks) fits SDS®

Use In: Rotary hammer with SDS chuck or SDS adapter

Size Range: 5/32" x 6" to 5/8" x 8"

Designed to be used in rotary hammer equipment with a slotted drive shank. Available in Bulk Pack quantities only - with the large volume user in mind. These bits meet and are manufactured to conform with ANSI standard B212.15 and can be used in concrete, block, brick and soft stone.

Cat. No.	Description	Usable Length	Std. Box	Std. Ctn.
0801	5/32" x 6"	4"	25	500
0803	3/16" x 4"	2"	25	450
0805	3/16" x 6"	4"	25	500
0807	3/16" x 8"	6"	25	450
0809	3/16" x 10"	8"	25	300
0811	7/32" x 6"	4"	25	500
0813	7/32" x 8"	6"	25	450
0815	7/32" x 10"	8"	25	300
0817	1/4" x 4"	2"	25	450
0819	1/4" x 6"	4"	25	500
0821	1/4" x 8"	6"	25	450
0823	1/4" x 10"	8"	25	300
0825	5/16" x 6"	4"	25	500
0827	3/8" x 6"	4"	25	300
0829	1/2" x 6"	4"	15	180
0831	5/8" x 8"	6"	15	120

\* SDS® is a registered trademark of Robert Boche Co.

## SDS-Max®

Use In: Rotary hammer with SDS-Max® chuck

Size Range: 1/2" x 13" to 1-1/2" x 23"

Designed for use in a rotary hammer equipped with a SDS-Max® type chuck. The bits are manufactured to conform with ANSI Standard B212.15 and can be used to drill in concrete, block, brick, and soft stone.

### 4-x Cutter SDS-Max® Drill Bit Sizes

Cat. No.	Size	Usable Length	Std. Tube
8801†	1/2" x 13"	8"	1
8802†	1/2" x 21"	16"	1
8805†	9/16" x 13"	8"	1
8809	5/8" x 13"	8"	1
8810	5/8" x 21"	16"	1
8812	5/8" x 36"	31"	1
8815	11/16" x 21"	16"	1
8817	3/4" x 13"	8"	1
8818	3/4" x 21"	16"	1
8820	3/4" x 36"	31"	1
8829	7/8" x 13"	8"	1
8830	7/8" x 21"	16"	1
8833	1" x 13"	8"	1
8834	1" x 21"	16"	1
8836	1" x 36"	31"	1
8843	1-1/8" x 15"	10"	1
8844	1-1/8" x 23"	18"	1
8846	1-1/4" x 15"	10"	1
8847	1-1/4" x 23"	18"	1
8848	1-1/4" x 36"	31"	1
8853	1-3/8" x 23"	18"	1
8859	1-1/2" x 23"	18"	1

† 1/2" and 9/16" sizes have a single tip and standard helical fluting. SDS-Max is a registered trademark of Robert Boche Co.

Industrial  
Grade  
SDS® Type

**NEW**

# Carbide Drill Bits

## Spline

Use In: Rotary hammer with Spline chuck

Size Range: 3/8" x 8" to 2" x 23"

Designed for use in a rotary hammer equipped with a spline type chuck. The bits are manufactured to conform with ANSI Standard B212.15 and can be used to drill in concrete, block, brick, and soft stone. Both 4-X Cutter and single tip head styles are available.

### 4-x Cutter Head Spline Carbide Drill Bits

Cat. No.	Size	Usable Length	Std. Tube
7017	5/8" x 10"	5"	1
7020	5/8" x 16"	11"	1
7021	5/8" x 23"	18"	1
7031	3/4" x 11"	6"	1
7033	3/4" x 16"	11"	1
7035	3/4" x 23"	18"	1
7036	3/4" x 27"	22"	1
7037	3/4" x 36"	31"	1
7043	7/8" x 16"	11"	1
7045	7/8" x 23"	18"	1
7049	1" x 16"	11"	1
7051	1" x 23"	18"	1
7053	1" x 36"	31"	1
7057	1-1/8" x 16"	11"	1
7059	1-1/8" x 23"	18"	1
7064	1-1/4" x 16"	11"	1
7066	1-1/4" x 23"	18"	1
7069	1-1/4" x 36"	31"	1
7072	1-3/8" x 23"	18"	1
7077	1-1/2" x 23"	18"	1

### Single Tip Spline Carbide Drill Bits

Cat. No.	Size	Usable Length	Std. Tube
1401	3/8" x 8"	3"	1
1402	3/8" x 11"	5"	1
1403	3/8" x 16"	11"	1
1405	7/16" x 13"	8"	1
1407	1/2" x 10"	5"	1
1408	1/2" x 13"	8"	1
1409	1/2" x 16"	11"	1
1410	1/2" x 22"	18"	1
1412	1/2" x 27"	22"	1
1413	1/2" x 36"	31"	1
1415	9/16" x 13"	8"	1
1418	5/8" x 10"	5"	1
1419	5/8" x 13"	8"	1
1420	5/8" x 16"	11"	1
1421	5/8" x 22"	18"	1
1424	5/8" x 36"	31"	1
1427	11/16" x 13"	8"	1
1431	3/4" x 10"	5"	1
1433	3/4" x 16"	11"	1
1434	3/4" x 22"	18"	1
1436	3/4" x 27"	22"	1

### Single Tip Spline Carbide Drill Bits, continued

Cat. No.	Size	Usable Length	Std. Tube
1437	3/4" x 36"	31"	1
1443	7/8" x 16"	11"	1
1444	7/8" x 22"	18"	1
1446	7/8" x 36"	31"	1
1449	1" x 16"	11"	1
1450	1" x 22"	18"	1
1453	1" x 36"	31"	1
1457	1-1/8" x 16"	11"	1
1458	1-1/8" x 22"	18"	1
1464	1-1/4" x 16"	11"	1
1465	1-1/4" x 22"	18"	1
1470	1-3/8" x 16"	11"	1
1471	1-3/8" x 22"	18"	1
1477	1-1/2" x 22"	18"	1
1486	1-3/4" x 22"	18"	1
1490	2" x 22"	18"	1

### HD Straight Shank Bits

Use In: Hammer drill

Size Range: 1/8" x 3" to 3/4" x 24"

Designed for use in a hammer drill equipped with a 3 jaw Jacobs type chuck. The bits meet ANSI standards and can be used to drill in concrete, block, brick, and soft stone.

Cat. No.	Drill Size	Usable Length	Shank Size	Std. Pouch
0501	1/8" x 3"	2-1/4"	1/8"	1
0503	5/32" x 6"	4"	5/32"	1
0504	3/16" x 4"	2-3/4"	3/16"	1
0505	3/16" x 6"	4"	3/16"	1
0512	1/4" x 4"	2-3/4"	1/4"	1
0513	1/4" x 6"	4"	1/4"	1
0514	1/4" x 13"	11"	1/4"	1
0516	1/4" x 24"	22"	1/4"	1
0519	5/16" x 6"	4"	5/16"	1
0522	3/8" x 6"	4"	3/8"	1
0523	3/8" x 13"	11"	3/8"	1
0525	3/8" x 24"	22"	3/8"	1
0531	1/2" x 6"	4"	3/8"	1
0532	1/2" x 13"	11"	3/8"	1
0534	1/2" x 24"	22"	3/8"	1
0538	5/8" x 6"	4"	1/2"	1
0540	5/8" x 13"	11"	1/2"	1
0545	3/4" x 6"	4"	1/2"	1
0547	3/4" x 13"	11"	1/2"	1
0548*	3/4" x 24"	22"	1/2"	1

\* Discontinued item once current stock exhausted.

5/8" and larger, shank is hex shaped.

### Bulk Pack

Cat. No.	Drill Size	Bits Per Pack
0593	1/4" x 4"	25
0594	1/4" x 6"	25
0595	3/8" x 6"	10

4-X  
Cutter  
Spline

Single  
Tip  
Spline

HD  
Straight  
Shank

# Carbide Drill Bits

IG Straight Shank

## IG Straight Shank Bits

Use In: Hammer Drill

Size Range: 1/8" x 3" to 1" x 12"

Designed for use in a hammer drill equipped with a 3 jaw Jacobs type chuck. The bits meet ANSI standards and can be used to drill in concrete, block, brick, and soft stone.

Cat. No.	Drill Size	Usable Length	Shank Size	Std. Pouch
0601	1/8" x 3"	2-1/4"	1/8"	1
0604	3/16" x 4"	2-3/4"	3/16"	1
0605	3/16" x 6"	4"	3/16"	1
0612	1/4" x 4"	2-3/4"	1/4"	1
0613	1/4" x 6"	4"	1/4"	1
0614	1/4" x 12"	10"	1/4"	1
0618	5/16" x 4"	2-3/4"	1/4"	1
0619	5/16" x 6"	4"	1/4"	1
0621	3/8" x 4"	2"	1/4"	1
0622	3/8" x 6"	4"	1/4"	1
0623	3/8" x 12"	10"	5/16"	1
0625	3/8" x 24"	22"	5/16"	1
0626	7/16" x 6"	4"	3/8"	1
0631	1/2" x 6"	4"	3/8"	1
0632	1/2" x 12"	10"	3/8"	1
0635	9/16" x 6"	4"	3/8"	1
0638	5/8" x 6"	4"	3/8"	1
0640	5/8" x 12"	10"	3/8"	1
0645	3/4" x 6"	4"	1/2"	1
0647	3/4" x 12"	11"	1/2"	1
0650	7/8" x 12"	10"	1/2"	1
0654	1" x 12"	10"	1/2"	1

## Bulk Pack

Cat. No.	Drill Size	Bits Per Pack
0561	3/16" x 4"	50
0562	3/16" x 6"	50
0563	1/4" x 4"	25
0564	1/4" x 6"	25
0565	3/8" x 6"	10
0566	1/2" x 6"	10

"A" Taper

## "A" Taper Drill Bits

Use In: Rotary hammer with "A" Taper chuck or Adapter

Size Range: 1/4" x 6" to 3/4" x 12"

Designed for use in a rotary hammer equipped with an "A" Taper type chuck. The bits meet ANSI standards and can be used to drill in concrete, block, brick, and soft stone.

Cat. No.	Drill Size	Usable Length	Std. Tube
0712	1/4" x 6"	4"	1

## "A" Taper Shank Adapters

Cat. No.	Size	Std. Pouch
0790*	SDS-Max® to "A" Taper	1
0798*	Ejector Pin "A" Taper	1

\* Discontinued item once current stock exhausted.

## Rotary Carbide Drills

Use In: Rotary Only Drill

Size Range: 1/8" x 2-1/2" to 3/4" x 6"

Designed for use in a rotation only drill equipped with a 3 jaw Jacobs type chuck, the bits meet ANSI standards with a positive rake tip and can be used to drill in soft or brittle masonry materials using rotation only. Fast spiral flutes are for fast drilling in soft to medium masonry materials such as block or brick. Deep fluted drills perform best in concrete where the wide fluting helps clean concrete chips and dust from the hole.

## Fast Spiral

Cat. No.	Drill Size	Shank Size	Usable Length	Overall Length	Std. Tube
8500	1/8"	1/8"	1-3/4"	2-1/2"	1
8506	3/16"	3/16"	1-3/4"	3"	1
8508	1/4"	1/4"	1-3/4"	4"	1
8512	5/16"	1/4"	2-1/2"	4"	1
8514	3/8"	1/4"	2-1/2"	4"	1
8560	3/8"	1/4"	4-1/2"	6"	1
8562*	3/8"	1/4"	16-1/2"	18"	1
8520	1/2"	3/8"	4"	6"	1
8566*	1/2"	3/8"	10"	12"	1
8526	5/8"	1/2"	4"	6"	1
8570	5/8"	1/2"	10-1/2"	12"	1
8530	3/4"	1/2"	4"	6"	1

\* Discontinued item once current stock exhausted.

## Deep Flute

Cat. No.	Drill Size	Shank Size	Usable Length	Overall Length	Std. Tube
8606	3/16"	3/16"	1-3/4"	3"	1
8608	1/4"	1/4"	1-3/4"	4"	1

Rotary

# Carbide Drill Bits

## Rebar Cutter

Use With: Rotation-only drill with standard 1/2" Jacobs style chuck  
Size Range: 1/2" to 1-1/4" diameter

Rebar cutter bits provide a quick, easy method for drilling through mesh or reinforcing bars embedded in concrete when the drilled hole cannot be relocated. The bits are used in the rotation only mode and are designed to fit in a standard rotary drill motor with a 1/2" Jacobs style chuck.

Cat. No.	Size	Usable Length	Std. Box
0845	1/2" x 12"	11"	12
0844	9/16" x 12"	11"	12
0846	5/8" x 12"	11"	12
0847	11/16" x 12"	11"	12
0849	3/4" x 12"	11"	12
0851	7/8" x 12"	11"	12
0853	1" x 12"	11"	12
0855	1-1/4" x 12"	11"	12

## Heavy Duty Chisels

Use In: Combination Rotary Hammer / Chipping Tool with a Spline, SDS-Max® or 3/4" Hex Chuck

Size Range: Bull Point, Flat, Scaling and Bushing

Heavy Duty Chisels and accessories are designed for use in a combination rotary hammer / chipping tool equipped with a Spline, SDS-Max®, or 3/4" Hex chuck. The chisels can be used for chipping applications in concrete, block, brick, and soft stone.

Cat. No.	Shank Type	Description	Std. Box
0950	Spline	Bull Point Chisel 12"	1
0951	Spline	Bull Point Chisel 18"	1
0952	Spline	Flat Chisel 1" x 12"	1
0953	Spline	Flat Chisel 1" x 18"	1
0954	Spline	Scaling Chisel 1-1/2" x 12"	1
0955	Spline	Scaling Chisel 2" x 12"	1
0959	Spline	Ground Rod Driver 7/8" x 10-1/4"	1
0960	Spline	Bushing Tool 1-3/4" x 9-1/4"	1
0965	SDS-Max®	Bull Point Chisel 12"	1
0966	SDS-Max®	Bull Point Chisel 18"	1
0967	SDS-Max®	Flat Chisel 1" x 12"	1
0968	SDS-Max®	Flat Chisel 1" x 18"	1
0969	SDS-Max®	Scaling Chisel 1-1/2" x 12"	1
0970	SDS-Max®	Scaling Chisel 2" x 12"	1
0974	SDS-Max®	Ground Rod Driver 7/8" x 10-1/4"	1
0975	SDS-Max®	Bushing Tool 1-3/4" x 9-1/2"	1
0982	3/4" Hex	Flat chisel 1" x 12"	1
0983	3/4" Hex	Flat chisel 1" x 18"	1

\*Discontinued item once current stock exhausted.

## Heavy Duty One and Two Piece Core Bits

Use In: Rotary hammer with a Spline or SDS-Max® chuck  
Size Range: 1-1/2" to 5"

Designed for use in a rotary hammer equipped with a spline or SDS-Max® type chuck. The bits can be used to drill in concrete, block, brick, and soft stone.

### One Piece Spline Core Bits - Heavy Wall

Cat. No.	Drill Size	Description	Std. Tube
0260*	2-5/8"	Hollow Core Bit Spline 2-5/8" x 22"	1

One piece core bits are packaged with a centering bit and ejector pin.

\* Discontinued item once current stock exhausted.

### One Piece SDS-Max® Core Bits - Heavy Wall

Cat. No.	Drill Size	Description	Std. Tube
0284	2-5/8"	Hollow Core Bit SDS-Max 2-5/8" x 22"	1

One piece core bits are packaged with a centering bit and ejector pin.

### Two Piece Core Bits - Heavy Wall

Cups with external male rope thread

Cat. No.	Drill Size	Description	Std. Tube
0570	1-3/4"	Hollow Core Bit 1-3/4" x 4"	1
0571	2"	Hollow Core Bit 2" x 4"	1
0572	2-5/8"	Versio Core Cutter 2-5/8" x 4"	1
0573	3-1/8"	Versio Core Cutter 3-1/8" x 4"	1
0575	4"	Versio Core Cutter 4" x 4"	1
0576	5"	Versio Core Cutter 5" x 4"	1

### Two Piece Core Bits

Drive shanks with internal female rope thread

Cat. No.	Shank Type	Description	Overall Length	Usable Length	Std. Tube
0578	Spline	Adaptor	7"	2"	1
0580	SDS-Max®	Adaptor	7-3/4"	2-3/4"	1
0582	-	Extension	11" (w/o flute)	11"	1

Rebar Cutter



Chisel



Heavy Duty Core Bits

POWERS FASTENERS **BRANCH INFORMATION****USA LOCATIONS**

CITY	ADDRESS	CONTACT	PHONE	FAX
Alabama	5405 Buford Hwy Suite 410 Norcross, GA 30071-3984	Jeff Hatchett	205-520-6044	678-966-9242
Atlanta	5405 Buford Hwy Suite 410 Norcross, GA 30071-3984	Robert Brito	678-966-0000	678-966-9242
Boston	2 Powers Lane, Brewster, NY 10509	Jack Armour	800-524-3244	914-576-6483
Charlotte	349 L West Tremont Avenue, Charlotte, NC 28203	Bob Aurisy	704-375-5012	704-376-5517
Chicago	2472 Wisconsin Avenue, Downers Grove, IL 60515	Dan Gilligan	630-960-3156	630-960-3912
Dallas	10625 King Williams Drive, Dallas, TX 75220	Kyle Thuenemann	972-506-9258	972-506-9290
Denver	2475 West Second Street #35, Denver, CO 80223	Aaron Minnis	303-922-9202	303-922-9228
Detroit	21600 Wyoming Avenue, Oak Park, MI 48237	Glen Gaskill	248-543-8600	248-543-8601
Florida	9208 Palm River Road, Bldg. 3, Suite 305, Tampa, FL 33619	Mark Mamula	813-626-4500	813-626-4545
Houston	13833 North Promenade, Suite 100, Stafford, TX 77477	Chris Salisbury	281-491-0351	281-491-0367
Indianapolis	15290 Stony Creek Way, Noblesville, IN 46060	Bill Trainor	317-773-1668	317-773-1690
Kansas City / St Louis	716 East 16th Avenue, North Kansas City, MO 64116	Don James, Jr.	816-472-5038	816-472-5040
Los Angeles	2761 Dow Avenue, Tustin, CA 92780	Jack Stewart	714-731-2500	714-731-2566
Maryland	3137-B Pennsy Drive, Landover, MD 20785	Chris Van Syckle	301-773-1722	301-341-5119
Milwaukee	12020 W. Feerick Street, Milwaukee, WI 53222	Donn Raduenz	414-466-2400	414-466-3993
Minneapolis	351 Wilson Street, NE Minneapolis, MN 55413	Rick Gruye	612-331-3756	612-331-3549
Nashville/Memphis	221 Blanton Avenue, Nashville, TN 37210	Ira Liss	615-248-2667	615-248-2676
New Orleans	102 Sampson Street, Houston, TX 77003	Cal Zenor	713-228-1524	713-228-1528
New York	2 Powers Lane, Brewster, NY 10509	John Partridge	914-235-6300	914-576-6483
Philadelphia	2 Powers Lane, Brewster, NY 10509	Greg Stephenson	800-524-3244	914-576-6483
Phoenix	3602 E. Southern Ave, Suite 5 Phoenix, AZ 85040	Craig Hering	602-431-8024	602-431-8027
Pittsburgh	1360 Island Avenue, McKees Rocks, PA 15136	Bill Dugan	412-771-3010	412-771-9858
Portland	129 South Kenyon, Seattle, WA 98108	Jim Swink	360-608-6845	206-762-5817
Rochester	40 Harrison Street, Rochester, NY 14605	Mike Kolstad	585-288-2080	585-288-8732
Salt Lake City	2212 SW Temple #20, Salt Lake City, UT 84115	Don Manning	801-466-9428	801-466-3083
San Francisco	28970 Hopkins Street, Suite B+C, Hayward, CA 94545	Dan Mullan	510-293-1500	510-293-1505
Seattle	129 South Kenyon, Seattle, WA 98108	Darin Arnold	206-762-5812	206-762-5817

**INTERNATIONAL LOCATIONS**

COUNTRY/REGION	ADDRESS	CONTACT	PHONE	FAX
Australia	Factory 3, 205 Abbots Road, Dandenong, South Victoria 3175	Phil Rose	+61 3 8787 5888	+61 3 8787 5899
Canada	6950 Edwards Blvd. Mississauga, Ontario L5T 2W2	Mark Russell	905-673-7295	905-673-6490
China	Metropolitan Business Centre, East Nandan Road, Lane 300, No. 9, Room 604 Xuhui District, Shanghai, China 200030	Jake Olsen	+86-21-3363-2880	+86-21-3363-2881
China	Trif International, 4E, Building 11, The City of Design, Tianmian Village, Futian, Shenzhen 518000	Tom Nie	86-755-82795378	86-755-82795379
Europe	Westrak 208, 1771 SV Wieringerwerf, Netherlands	Paul Geuvers	+31 888 769 377	+31 227 594 759
India	112, D Wing, Twin Arcade, Military Rd., Andheri, [E] Mumbai, 400059	Ajay Kulkarni	91-22-401591304	
Manitoba	1810 Dublin Avenue Man. Winnipeg, R3H 0H3	Distributor	204-633-0064	204-694-1261
New Zealand	PO Box 302 076 North Harbour Auckland	Claye Sesto	+64 9415 2425	+64 9415 2627
Quebec	721 Meloche Avenue, Dorval, Quebec H9P 2S5	Alan Hill	514-631-4216	514-631-2583
Thailand	80/89 MOO4 Petchakasem Road, Bangkae Bangkok 10160	Chalee Surakavanichakorn	+661 826 5821	

**LATIN & CARIBBEAN DISTRIBUTION INQUIRIES**

COUNTRY/REGION	ADDRESS	CONTACT	PHONE	FAX
Latin America	9208 Palm River Road, Ste 305, Tampa, Florida 33619	Michael Gaffigan	954-914-6665	813-626-4545

**LATIN & CARIBBEAN DISTRIBUTION**

COUNTRY/REGION	ADDRESS	CONTACT	PHONE	FAX
Brazil	HARD, Rua Dr. Humberto Pinheiro Viera, 150 Lote B, 1 B Distrito Industrial, Joinville, Brazil		55-47-40097209	55-47-40097217
Colombia	Electrogeno, S.A., Carrera 52 #71c-38, Bogota, Colombia		(57) 1 6600 9436	
Costa Rica	Electro Mechanics Supply, La Uruca Contiguo Banco Ntl., De Costa Rica Condominio, Horizontal Bodega #9, San Jose, Costa Rica		(506) 2233-2595	
Dominican Republic	Calle Estancia Nueva #17 E Esquina Cul-De-Sac 9, San Geronimo, Santo Domingo	Rodfor Team	809-224-5615	809-472-8640
Ecuador	Acero Comercial Ecuatoriano S.A., Av. La Prensa N45-14 y Telégrafo 1 – Quito Av. Juan Tanca Marengo Km. 1.7 – Guayaquil	infoio@acero comercial.com infofy@acero comercial.com	(593-2) 2454 333 (593-4) 2683 060	(593-2) 2454 455 (593-4) 2683 059
Guatemala	Tecnofijaciones, 6 Avenue 8-56 Zona 9, Zona 9, Guatemala	Oscar Lucas Penagos	502-233-4-3478	
Panama	Centro-Industrial, Vía Cincuentenario, No. 7910, Ciudad Panama, Panama		(507) 302-8022	
Peru	Powers Peruana SAC, Av. Santa Catalina, 555 La Victoria, Lima 13, Peru (www.powersperuana.com)	Martin Vasquez	(011) 511 265 8500	(011) 511 330 0909
Venezuela	Calle Sucre/Qta. Maudora, #1721 Entre Cec Acosta Y San Ignacio Chacao, Caracas	Distributor	58 212 264 1313	58 212 263 0219
Trinidad - Tobago	Ft. Farfan, 3-5 Ibis Avenue, Ibis Acres, San Juan	Derek Cumming	(868) 674-7896	

Note: The information and data contained within this documentation was current as of September 2010. The information is for marketing purposes only and is subject to change and updates as needed. Powers Fasteners, Inc. reserves the right to change designs and specifications without notice or liability for such changes. Please contact Powers Fasteners for the most current and up to date available information or refer to our website at [www.powers.com](http://www.powers.com)

**Powers Fasteners** 2 Powers Lane, Brewster, NY 10509 P: (914) 235-6300 F:(914) 576-6483  
**Powers Fasteners Canada Ltd.** 6950 Edwards Boulevard Mississauga Ontario L5T-2W2 Canada  
P: (905) 673-7295 or 1-800-387-3480 F: (905) 673-6490

**Jobsite  
Assistance  
24/7**

