


DETAIL & SUBMITTAL SHEET



SPECIFICATIONS:

- Door: 14 ga. steel
- Trim: 18 ga. steel
- Finish: Primed grey baked enamel
- Latches: Flush, stainless steel cam latch
- Hinge: Full length piano hinge allows door to open to 180°

OPTIONS (at additional cost)


Finishes:

- Stainless Steel Type 304 No. 4 Satin Finish Brushed
- Stainless Steel Type 316 No. 4 Satin Finish Brushed


Options: (additional cost)

- WB 151 Key Code Cylinder locks keyed alike with 2 keys per lock
- Weather resistive neoprene gasket: 3 sides (Closed cell sponge, blend of Neoprene/EPDM/SBR. Meets ASTM D-1056: SCE 41, RE 41, 2A1; substrate UL 94HF-1 recognized.)
- Special sizes available
-

FRONT ELEVATION



SECTION DETAIL



When access is a requirement without a framed opening, our precision fit surface mounted access door is the solution in all types of walls and ceilings. The frame is laser cut from one sheet of steel for visual aesthetics with no recess.

✓	Item No.	Door Size W x H	Inside Door Opening	Cam Latch	Ship Wt. Lbs.
	SMP 120	8 x 8	8 x 7 3/4	1	4
	SMP 120	12 x 12	12 x 11 3/4	1	5
	SMP 120	16 x 16	16 x 15 3/4	3	10
	SMP 120	18 x 18	18 x 17 3/4	3	14
	SMP 120	24 x 24	24 x 23 3/4	4	18

Project: _____ Date: _____

Contractor: _____ Architect: _____

Sizes: _____ Quantity: _____ Approval Initials: _____



Corporate Office: 1330 Progress Drive • Front Royal, VA 22630
Phone: 1-800-255-5515 • Fax: 1-800-822-5001

www.wbdoors.com